VISIBLE EMISSION NOTAT	TIONS			
Inspector:	compton			
Date of Inspection:	11/11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift	ft Ind T	me: 5:00AM		
- Unit	Visual		Comments	
	Inspection NORMAL			
	or <u>ABN</u> ORMAL		-	
Visible Emission From Shaker	Nov	Editoria de la companya del companya del companya de la companya d		
Visible Emission From Discharge Conveyor System	Nov			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		_	
Inspector: Ale windle	Hernand-	2		
Date of Inspection:	1-11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shi	ft 15+ Time	5 <b>o</b> m		
Unit	Visual		Comments	
	Inspection			
The second secon	<u>NORMAL</u>			
	or		•	
And the state of t	ABNORMAL		***************************************	
Visible Emission From Shaker	Nov			
Visible Emission From				
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	o Comptor	"\		
Date of Inspection:				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	ime: 500 AM		
- Unit	Visual Inspection		Comments	
	<u>NORMAL</u>			
733 feet and the second	or ABNORMAL		-	
Visible Emission From Shaker	Nax	en e		
Visible Emission From Discharge Conveyor System	N/ .	- Name of the control		
	/ V & V			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Alexandr	o Hernano	42		
Date of Inspection:	2-11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift 1st Tin	1e: 5pw		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_	
Inspector:	1 Compte	VI		
Date of Inspection: 8/3	/1/			
	nift T	ime: 5:00 A M		
La	Visual		Comments	
	Inspection NORMAL or			
	ABNORMAL			
Visible Emission From Shaker	Non	solate transport for classical data and other management of the contract of th		
Visible Emission From Discharge Conveyor System	N	photographic designs and the same management and the same		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Alfandr	o Herna	ndez		
Date of Inspection:	~ · ·	1		
1	8-3-1	Prince of the Control		
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift 15 Ti	me: SDW		
- Unit	- Visual		Comments	
	Inspection			
The second secon	NORMAL			
	or			
The state of the s	ABNORMAL			
Visible Emission From Shaker	NOR	c-construction of the construction of the cons		
Visible Emission From				
Discharge Conveyor System	NOR	•		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS /			
Inspector:	Comptor			
Date of Inspection:	11 /			
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> Si	hift Ti	ime:		
Umt	Visual		Comments	
	Inspection NORMAL or ABNORMAL			
Visible Emission From Shaker	ABNORWAL	1		
VISIDIE EIIISSIUIT TUIT GITAKEI	Nos	$\label{eq:control_control_control} problem = problem =$		
Visible Emission From Discharge Conveyor System	<i>a</i> /			
	I W.	The state of the s		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

VISIBLE EMISSION NOTAT	HONS			
	nandez			
Date of Inspection: 8-4	! 1			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shif	t 15+ Tin	me: 50M		
Visible Emission From Shaker	- Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS	to a	<u> </u>	
Inspector: Alfundo He	mandez			
	4-11			,
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift 15# Ti	me: 50M		
Unit	- Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	NOR		·	
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATION Inspector:	rions npton			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shi	ft Ti	me: 5:00AM	Comments	
Entt	Inspection <u>NOR</u> MAL or ABNORMAL			`
Visible Emission From Shaker	Nov	e de construire		
Visible Emission From Discharge Conveyor System	Noc			

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS		<b></b> -,	
Inspector:	lemander			
Date of Inspection:	ZIIIWVIU Z		-	
8-3	<u> </u>		_	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift 15 Ti	me:		
Unit	Visual	T XXX	Comments	
	Inspection			
To the state of th	NORMAL			
	or ABNORMAL	. "	•	· ·
Visible Emission From Shaker	NICH			
	<u> </u>			
Visible Emission From				
Discharge Conveyor System	NIMD			
	IVUE			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS	<i>C</i>		
Inspector:	J CONAT	The second		
Date of Inspection:	· V			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shi	ift Ti	me: 5-06AIV		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments	,
Visible Emission From Shaker	Noc	*4EEE gaezze een siin 1755 for de door gegelle een 1500 eeu van de door gegels van de door de		
Visible Emission From Discharge Conveyor System	Nax			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:	J	·		
Date of Inspection:	8611			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	lift Ti	me: 17:00		
. Unit	Visual		Comments	
	Inspection NORMAL			
All Maries and All Ma	or ABNORMAL	· ·		
Visible Emission From Shaker	Na	ATOU Dun		
Visible Emission From Discharge Conveyor System	Noc	Ú		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS		]	
Inspector: Ted Co-	ptor	-	
Date of Inspection: 8/7///	V	_	
Shift: 1st Shift or 2nd Shift	Time: 5:00AV	Comments	
Unit Vis	ction		,
ABNO			
Visible Emission From Shaker	And the President Control of Cont		
Visible Emission From Discharge Conveyor System			

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATION Inspector: Date of Inspection: Shift: If Shift or 2 <sup>nd</sup> Shift	Time: 17:00	
Shirt. If Gills	Comments	
	Visual nspection NORMAL or BNORMAL	
Visible Emission From Shaker \	A DU DUM	
Visible Emission From Discharge Conveyor System	Jan V	

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

• Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS	5		
Inspector:	2 Compt			
Date of Inspection:	11	me: (200 A10)		
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> Shi	ift 2~0	5:00 HM	Comments	
Unit	Visual Inspection NORMAL			
	or ABNORMAL			
Visible Emission From Shaker	Noc	**************************************		
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Inspector:	
Date of Inspection:	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift Time:	
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	

Unit	Visual Inspection	Comments
Unit	NORMAL or	
Visible Emission From Shaker	<u>ABN</u> ORMAL	
Visible Emission From Discharge Conveyor System		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

**VISIBLE EMISSION NOTATIONS** 

VISIBLE EMISSION NOTA	ATIONS			
Inspector: RICK PAL	ono			
Date of Inspection: 8/9/1	1			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	_I	ime: 5800 AM		
Unit	Visual		Comments	
Visible Emission From Shaker	Inspection <u>NOR</u> MAL or ABNORMAL			
Visible Emission From Shaker	NOR	According 1990 CO		
Visible Emission From Discharge Conveyor System	NOR	**************************************		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	1 Compton			
Date of Inspection:	11			
-01	<u> </u>		,	
Shift: 1st Shift or 2nd Sh	"st "	me: 1700		
- Tight	Visual		Comments	
	Inspection NORMAL			
	or ABNORMAL		-	·
Visible Emission From Shaker	Nov	ng et still hindricht eine geleit der vertre dem still eine der der der der der der der der der de		
Visible Emission From Discharge Conveyor System	Nor	. The little desired the contract of the contr		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		_		
Inspector: RICK F	ALOMO				
Date of Inspection: 8/10	/11				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	rift Ti	ime: 5300AM	-		
L Distriction Unit	Visual			Comments	
	Inspection NORMAL		4.		
	or <u>ABN</u> ORMAL				·
Visible Emission From Shaker	NOR	The American Activities and Conference of the Co			
Visible Emission From					
Discharge Conveyor System	NOR	And the control of th			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	1 Compto	, <u>~</u>		
Date of Inspection:	111 6			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift T	ime: 760		
Unit	Visual Inspection <u>NORMAL</u> or <u>ABN</u> ORMAL		Comments	
Visible Emission From Shaker	n/o/	46 concession as server from the Colonian State Service State Service State Service Service State Service State Service State Service Service State Service State Service Service State Service State Service Service Service Service State Service Se	geographical des en and a second description of the second description	
Visible Emission From Discharge Conveyor System	Nor	4-th schoolstaning Constitution and Cons		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA- Inspector:	rions PACom	C		
Date of Inspection:	2/11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Tir 2nd	me: 5100AA	Comments	
Unit	Visual Inspection <u>NOR</u> MAL or			
Visible Emission From Shaker	ABNORMAL	while design and the second and the		
Visible Emission From Discharge Conveyor System	NOR	Supplemental control and a con		

Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.

 Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS ,			
Inspector: Ted Compitor			
Date of Inspection: 8/12/1/			
Shift: (1 <sup>st</sup> )Shift or 2 <sup>nd</sup> Shift T	ime: (70°)		
Unit Visual Inspection NORMAL or ABNORMAL		Comments	,
Visible Emission From Shaker			
Visible Emission From Discharge Conveyor System			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

Revised 2/10/09

D.1.12 Daily Visible Emissions Notations Per Each Daylight Shift Spent Carbon Place Carbon D. 1. CARBON ADSORPTION MONITORING LOG FOR DAILY AND QUARTERLY Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.10 Carbon Adsorber/Canister Monitoring

Condition D.1.17 Record Keeping Requirements (c)

Condition D.1.17 Record Keeping Requirements (c)

PCI shall document compliance by monitoring for VOC breakthrough is detected as stated below under Note. VISIBLE FMICCION .. PCI shall document compliance by monitoring for the carbon canister when breakthrough is detected as stated below under Note and the tanks are in operations. PCI shall replace the carbon canister when breakthrough is detected as stated below under Note. D.1.14 CARBON ADSORPTION SYSTEM INSPECTION UNIT DOWN Inspector: TIAN:

VISIBLE EMISSION NOTA	ATIONS,			
Inspector:	to or			
Date of Inspection: 8/13/	11			
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> ) Sh	nift 2nd Ti	me: 500AM		
Unit	Visual		Comments	
	Inspection NORMAL			
The state of the s	or <b>ABN</b> ORMAL		·	
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	Nor			


- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTAT	TONS			
Inspector:	1			
Details	Fl ga 1	j		
Date of Inspection:	U SI	13/11		
Shift: (1 <sup>st</sup> Shift or 2 <sup>na</sup> Shif	t Ti	me: 17-00		
Unit	Visual		Comments	
	Inspection			
	NORMAL		•	
	or ABNORMAL		· · · · · · · · · · · · · · · · · · ·	
Visible Emission From Shaker	- 1 A			
		~~~~		
Visible Emission From	, .			
Discharge Conveyor System	Nhi	Notation-		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	dCompto	7		
Date of Inspection:	114/1/			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nb</sup> Sh	ift In Ti	me: 500 AM		
Unit	Visual		Comments	
	Inspection			
	<u>NORMAL</u>		•	
The first of the control of the cont	or <u>ABN</u> ORMAL			
Visible Emission From Shaker	Nor			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.




VISIBLE EMISSION NOTA	TIONS		_	
Inspector: Morvin	2005			
Date of Inspection:	14-(1			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift Ti	me:		
Unit	Visual		Comments	
	Inspection			
	<u>NORMAL</u>			
The state of the s	or <u>ABN</u> ORMAL			
Visible Emission From Shaker	Nor	_appropriate_co.		
Visible Emission From Discharge Conveyor System	Noc	<u> </u>		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Alannaka	Jermandez			
Date of Inspection	- Carrier			
	<u> </u>			
Shift 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	rift T	me:		
Unit	Visual	Output I	Comments	
	Inspection			•
	NORMAL			
	or <b>ABN</b> ORMAL			
	ADIACINIAL	}		
Visible Emission From Shaker	NOR			
Visible Emission From				
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick PA	Lomo			
Date of Inspection: 8/16/	11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	_i	ime: 5800		
Unit	Visual		Comments	
The state of the s	Inspection NORMAL			
	or <b>ABN</b> ORMAL			
Visible Emission From Shaker	NOR	***		
Visible Emission From				
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	undra Her	nondez		
Date of Inspection:	3-11	0 - 1)		
Shift: \(\s^t \) Shift or \(2^{nd} \) Sh		ime: 5 DW		
Unit	Visual	en i	Comments	
	Inspection NORMAL			
Section 1 (1) (1) (1) (1) (1) (1) (1) (1) (1) (	or <b>ABN</b> ORMAL			
Visible Emission From Shaker	NOR	**************************************		
Visible Emission From Discharge Conveyor System	NOR	Assemble common and accommon for dissipation of constraints and an extended confidence company.		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.


V	/IS	IBL	F	F	M	IS	SI	O	N	N	U.	ΓΔ	T	0	N	2

TOIDEE EMICOION NO IATION		_	
Inspector:			
Date of Inspection:			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift	Time:		
Unit Visual	·	Comments	
Inspection			
<u>NOR</u> MAL			
or <b>Abn</b> ormal			
Visible Emission From Shaker			
Visible Emission From			
Discharge Conveyor System			
			*

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Alt MNOVO	Hernande	22		
Date of Inspection:	- 11			
8-1	1-11			
Shift: (1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	lift Ti	ime:		
Unit	Visual		Comments	
	Inspection			
	NORMAL			
	or		,	•
The second programmed by the control of the control	ABNORMAL		·	
Visible Emission From Shaker	NOR			
Visible Emission From	10-10-			
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTATIONS			
Inspector: KICK PALOMO			
Date of Inspection: 8 / 18 / 11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift	Time: 5:00AM		
Unit Visual		Comments	
Inspection NORMA			
or ABNORM	AL		
Visible Emission From Shaker NOR			
Visible Emission From Discharge Conveyor System			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Alexando	Hernandez			
Date of Inspection:	8-11.			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sl	nift 15t Ti	me: 5pm		
Unit	Visual		Comments	
	Inspection NORMAL			
	or <b>ABN</b> ORMAL		·	
Visible Emission From Shaker	NOR	and the administration of the state of the s		
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick M	Acono			
Date of Inspection: 8/19	14			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	me: S.OOAM	_	
Unit	Visual		Comments	
	Inspection			
A Company of the Comp	NORMAL			
	or ABNORMAL		e e e	
Visible Emission From Shaker	NOR	n period grant and the last of the profit of the last		
Visible Emission From				
Discharge Conveyor System	NOR	* Collection in more than the last the		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATIONS	<i>j</i>		
Inspector: Ted Comp	ton		
Date of Inspection:			
Shift: (1st Shift or 2nd Shift	Time: 1700		
Unif Visual Inspection NORMAL or ABNORMAL		Gomments	
Visible Emission From Shaker			
Visible Emission From Discharge Conveyor System			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Ted	Comptor	1		
Date of Inspection: 8/20/	(1)			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shi	ift 15+ T	ime: 1700		
- Unit	Visual	1	Comments	
	Inspection	ļ.		
	<u>NORMAL</u>	<u> </u>		
	or	. *		
Fig. 10 and the second	ABNORMAL			
Visible Emission From Shaker	a )			
	1Vov			
Visible Emission From				
Discharge Conveyor System	n1 -			
	VIV or	And the state of t		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.








VISIBLE EMISSION NOTATIONS	S			
Inspector: Ted Compt	e ~1			
Date of Inspection:				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift	Tin	ne: 5:00 AM		
	/isual		Comments	
Ins	pection DRMAL			
	or NORMAL			
Visible Emission From Shaker	0 V	* Memory regions a second space as second spac		
Visible Emission From Discharge Conveyor System	v ·			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:				
Date of Inspection:				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ti	me:		
Unit	Visual		Comments	- A andro Allanda and and
	Inspection NORMAL			
	or ABNORMAL			
Visible Emission From Shaker	Nac			
Visible Emission From Discharge Conveyor System	Noc			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.



VISIBLE EMISSION NOTA	TIONS			
Inspector: RICK PA	-lome			
Date of Inspection: 8/22	/11		name.	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift, T	ime: 5:00AM		
Unit	Visual		Comments	
	Inspection <u>NORMAL</u> or		5.	
Para Harris Company (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (1997) (19	ABNORMAL		. *	
Visible Emission From Shaker	NOR			·
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Aleinory	Hernandez			
, , , , , , , , , , , , , , , , , , ,	2-11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift 13t Tin	4		
		<u> </u>		
Unit	Visual		Comments	
	Inspection			
	NORMAL			
			·	
	or			
The state of the s	ABNORMAL			
Visible Emission From Shaker	100			
	NOK			
Visible Emission From				
Discharge Conveyor System	1.00			
2.55a.ge 25veyor eyatem	NOK			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Rick P	Homo			
Date of Inspection: 9/2				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift T	ime: 5100 AM		
L. L. Lunit	Visual		Comments	
	Inspection NORMAL			
	or <b>ABN</b> ORMAL			
Visible Emission From Shaker	NOR	n singuage de de Carlos de		
Visible Emission From Discharge Conveyor System	NOR	majoristististististististististististististi		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.





VISIBLE EMISSION NOTA	ATIONS			
Inspector: Alexandr	Hernant	2-2		
Date of Inspection:	-23-11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	lift St Ti	me: 5pm		
Unit	Visual		Comments	
	Inspection	· . ·		
And the state of t	NORMAL or		**************************************	
	ABNORMAL			
Visible Emission From Shaker	NOR			
Visible Emission From	4.1.			
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.







VISIBLE EMISSION NOTA	ATIONS			
Inspector: RickP	Alono			
Date of Inspection: $\delta/24$	1/11			
21	nift, Ti	ime: 5:00AM		
Unit	Visual		Comments	
	Inspection NORMAL			
And the control of th	or ABNORMAL		. *	•
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System		THE PROPERTY AND P		
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Aldiandra	Hernandez			
Date of Inspection:			www.declare.	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift 13+ Til	me: 50M		
Unit	Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS		•	
Inspector: RICK A	Lomo		]	
Date of Inspection: 8/25/	111			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh		ime: 5:00 AM		
Unit	Visual		Comments	
	Inspection			
	NORMAL		•	
The first part of the control of the	ABNORMAL		-	
Visible Emission From Shaker	h			
	NOR			
Visible Emission From				
Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTATION	SNC			
Inspector: Alexandra Hama	mde7			
Date of Inspection: 8-25-1				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Shift	15± Ti	me: SDW1		
	Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOT	ATIONS			
Inspector: Pick	PACOMO			
Date of Inspection:	26/15		-	
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sl	rift 2nd T	ime: 5, OGAM	~	
Unit	Visual Inspection <u>NORMAL</u> or		Comments	
Visible Emission From Shaker	ABNORMAL			
Visible Emission From	NOK	proposed and the second and the seco		
Discharge Conveyor System	NOC			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	ed Compt	v M		
Date of Inspection:	27/11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift 2nd Ti	me: 500 A M		
Unit	Visual		Comments	
	Inspection NORMAL			
The Control of the Co	or ABNORMAL	. ~	÷	
Visible Emission From Shaker	Nov	And of each of the state of the		
Visible Emission From Discharge Conveyor System	Nov	Committee the property of the committee		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Rick	PALOME			
Date of Inspection: 8/2	7/11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	end 15t Ti	me: 5:00 Am		
Unit	Visual		Comments	
Unit	Inspection NORMAL or			
	ABNORMAL			
Visible Emission From Shaker	NOK	and the second contraction of the second sec		
Visible Emission From Discharge Conveyor System	Non	National consequence Association and Consequence Associati		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:				
	77 Or -	+		
Date of Inspection:	8/28			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift Ti	ime: @ 0500		
Unit	Visual		Comments	
	Inspection			
	NORMAL			
	or			
A Company of the Comp	ABNORMAL	}		
Visible Emission From Shaker	NW	,,,animon		
Visible Emission From	*			
Discharge Conveyor System	Non	yangdana		
		(		

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTAT	TIONS			
Inspector:				
Date of Inspection:	200			
	7-28-1		_	
Shift: 1 Shift or 2 <sup>nd</sup> Shif	t Time	: 6100 on		
Unit	Visual Inspection <u>NORMAL</u> or ABNORMAL		Comments	
Visible Emission From Shaker	Nac			
Visible Emission From Discharge Conveyor System	Noc			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector:				
Date of Inspection:	5 70 11			
	20120111			
Shift: 1 <sup>st</sup> Shift or (2 <sup>nd</sup> Sh	iff Ti	me:		
Marian Ma	/			
- Unit	Visual		Comments	
n ar maidirí seo agus 1900 de 1900 formanta de la companya de la c	Inspection	f .		
A Company of the Comp	NORMAL			
	or		~	
	ABNORMAL			
Visible Emission From Shaker	s 20			
	Noll	n-years)		
Visible Emission From	į	, seemalingtoner-		:
Discharge Conveyor System	Nana			
	NAC			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector: Alexandro	Hernandez	•		
Date of Inspection: 8 - 2				
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	nift of Ti	me: 50M		
Unit	Visual Inspection NORMAL or ABNORMAL		Comments	
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	TIONS			
Inspector: Ale is not con	Hernande	de-		
Date of Inspection: 8-3	0-11			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift ist Ti	me: 5pM		
Unit	Visual Inspection NORMAL		Comments	
A second	or ABNORMAL			
Visible Emission From Shaker	NOR			
Visible Emission From Discharge Conveyor System	NOR			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.

VISIBLE EMISSION NOTA	ATIONS			
Inspector:	compton			
Date of Inspection: 8/3//	110			
Shift: 1 <sup>st</sup> Shift or 2 <sup>nd</sup> Sh	ift Ind	ime: 500 AW		
L Junit	- Visual		Comments	
	Inspection <u>NOR</u> MAL			
	or ABNORMAL			
Visible Emission From Shaker	Nov			
Visible Emission From Discharge Conveyor System	Nor			

- Visible inspection must be performed during normal daylight operations and during the part of operations that would normally be expected to cause the greatest emissions.
- Opacity is a measure of the degree to which emissions reduce the transmission of light and obscure the view of an object in the background.